

DISASTER RECOVERY



SAT COLT

TRUCK SPECIFICATIONS

- Ford F-750 SBA 4X2 32,000-lb GVW de-rated to 25,999-lb GVW
- 6.7L Powerstroke® 300 HP, 700 lb-ft Torque Diesel Engine with Block heater
- 10,000-lb Front Axle with 10,000-lb Suspension, 14-Ply G-Rated Tires
- 21,000-lb Rear Axle with 21,000-lb Suspension, 14-Ply G-Rated Tires
- Ford TorqShift 6-Speed Double Overdrive Automatic Transmission
- 115 Gallon Fuel Capacity, 65 Gal (Left Side Tank), 50 Gal (Right Side Tank)
- Air Brakes, Polished Aluminum Wheels
- Preferred Equipment Package Includes; Cruise, Tilt, AC, SYNC Media System
- Chrome Bumper & Grille, Powder Coated Steps, Battery Box, and Air tanks
- Rear View Backup Camera, Cab-Mounted Work Lights

COLT SPECIFICATIONS & OPTIONS

Bed Frame and Accessories:

- Fully Galvanized, Custom Manufactured Bed Frame with LED Lighting
- (4) Stabilizing Outriggers with 7,000-lb Jacks
- (4) Automatic Hydraulic Leveling Jacks

Equipment Cabinet:

- U.L.® Listed NEMA 3R Communications Cabinet
- (2) 3.5-Ton HVAC Units with Lead-Lag Controller
- R56 Ground Ring, Main Ground Bar (Exterior) Equipment Ground Bar (Interior)
- 200 AMP 40 Position 1 Phase 3-Wire Distribution Panel
- Automatic Transfer Switch with MOV/SAD Surge Protector with Cam Locks for Alternate Source Connection
- R/F Entry Bulkhead, Interior & Exterior GFI Receptacles
- Telco Entrance with Interior Telco Board
- Dedicated Work Desk with Ample Storage

Mast:

- (1) 60' Pneumatic Heavy Duty Locking, 530-lb Capacity

Antenna Mount:

- Patent-Pending Tilt-Over 3-Sector Antenna Mount Allows for Permanent Coax Connectivity

1.8M Satellite Dish:

- 1.8M Dish with Auto Acquisition Controller
- AVL 1RU 1,000 Watt 48V BUC Power Supply

Generator:

- 20 Kw Diesel
- 1 Phase 120/240 Volt 82 Amp
- Integrated with Vehicle Fuel Tanks
- Block Heater and Battery Charger Included

NewMar DC Power System:

- Commander DC Power System
 - Input: 115/230 VAC
 - Output: 48 VDC, 6kW – 14kW
- (5) C2RX-2048 Rectifiers, (1) is Considered Spare
 - 41.7 Amp 2,000 watt
- 12 Breakers: (6) 50 Amp, (3) 30 Amp, (3) 20 Amp
- NewMar Inverter
 - 48-2000RM
- (8) Front Terminal Batteries (2 -48 Strings)

