Premium



TRAILER SPECIFICATIONS

- 8,000-lb. GVWR
- 5,000-lb. Tongue Jack
- 2,000-lb. Leveling Jacks (4)
- 12,000-lb. 2" Ball Hitch Vertically Adjustable
- 205/75/R15 Tires on 15" x 6" Rims with 1/2" Studs
- Spare Tire Included
- Conspicuity Markings

- 72" OSHA Compliant Crows Nest Mast Support Structure With Boarding Ladder
- Hot Dipped Galvanized, Universal Mounting, Steel Grating Trailer Deck
- Galvanized, Multiple Position Outriggers (4)
- Electric Brakes (Both Axles) With Emergency Break-Away
- Courtesy Kit—(2) Wheel Chocks, (4) Safety Cones, (4) Jack Pads
- Aluminum Storage Cabinet with Linex® Coated Interior

CONFIGURATION OPTIONS

Pneumatic Masts:

- 30' 150-lb. Payload Capacity
- 42' 300-lb. Payload Capacity
- 45' 800-lb. Payload Capacity (Proprietary Design)
- 59' 1,200-lb. Payload Capacity
- 60' 530-lb. Payload Capacity
- 76' 300-lb. Payload Capacity
- Protective Weather Cover Included
- Guy Kit Included

Equipment Cabinets:

- U.L.® Listed NEMA 3R Communications Cabinet
- 150 MPH Wind Load, 150-lb/sq. ft. Snow Load, 500lb/sq. ft. Floor Load, Zone 4 Rated
- HVAC Units as Required
- Multiple Location R/F Entry Ports Flexible Equipment Mounting Options with Ceiling Mounted Ladder Rack



Optional Generators:

- 10 Kw 1-Phase, 3-Wire, 120/240 Volt
- 15 Kw 1-Phase, 3-Wire, 120/240 Volt
- Block Heater and Battery Charger Included
- 24 or 48 Hour Fuel Cell

Options/Add-ons:

- Galvanized RRU Mounting Frame & Pipes
- 3-Sector Antenna Mounting System
- Mid-Level Microwave Mount
- Pan & Tilt Microwave Mount with Controller