

# SUN WEST ENGINEERING SPEC SHEET

Sun West Product - Mini Cow

| Description                         | Specification                      | Additional Info.            |
|-------------------------------------|------------------------------------|-----------------------------|
| <b>TRAILER SPECS</b>                |                                    |                             |
| Frame                               | C6/8.2 w/ 3" Cross Members         | Fully Hot-Dipped Galvanized |
| Trailer Frame Width                 | 72"                                |                             |
| Trailer Frame Length                | 180"                               |                             |
| Trailer Length Overall              | 201.00"                            |                             |
| Trailer Deck Height                 | 26.50"                             |                             |
| Trailer Gross Vehicle Weight (GVWR) | 8,000-lb. Max                      |                             |
| Trailer Gross Axle Weight (GAWR)    | 3,500-lb. ea/7,000 total           |                             |
| Trailer Approx. Ship Weight         | 4200-lb.                           |                             |
| Steel Grating Deck                  | Universal Mounting                 | Non-Skid                    |
| Number of Axles                     | 2 (Tandem)                         |                             |
| Standard Coupler Size               | 2-5/16", Ball Hitch, 12000-lb. Max | Vertically Adjustable       |
| Electric Brakes                     | Both Axles                         | Emergency Break-Away        |
| Number of Tires/ Inc. Spare         | 5                                  |                             |
| Tire Size                           | 205/75R15                          |                             |
| Tire Load Range                     | C                                  |                             |
| Tire P.S.I.                         | 50                                 |                             |
| Wheels/ Rim Size                    | 15" x 6" 5/4.5                     |                             |
| Wheel Studs                         | 1/2"                               |                             |
| Tongue Jack                         | 1                                  | 5,000-lb. Max               |
| Leveling Jacks                      | 4                                  | 2,000-lb. Max               |
| Outriggers                          | 4                                  | Multi-Position              |
| Conspicuity Markings                | Reflective                         | As Required                 |
| Storage Boxes Standard Size         | 24"W x 72"L x 16"H                 | Linux Coated/Locking        |
| Safety Chains                       | 2                                  | Adjustable                  |
| Hardware                            | Grade-8/Yellow Zinc                | Stainless As Required       |
| Lighting                            | LED                                |                             |
| Boarding Step                       | Integrated                         | OSHA approved               |
| Wheel Chocks                        | 2                                  |                             |
| Jack Pads                           | 16 x 16 x 1                        | 4                           |
| Utility Tool Box                    | As Required                        | Linux Coated Interior       |

|                   |                          |            |
|-------------------|--------------------------|------------|
| <b>Crows Nest</b> | 2" x 2" x .187 Wall Tube | Galvanized |
|-------------------|--------------------------|------------|

|             |                        |                       |
|-------------|------------------------|-----------------------|
| <b>Mast</b> |                        |                       |
| Mast        | 10.3-60                | 530-lb. Lift/Pay Load |
| Compressor  | TA-6052                | 120 Volt              |
| Controls    | Pneumatic Valve Type   |                       |
| Trip J Hook | 1                      |                       |
| Guy Kit     | Augers/Cables/Hardware | 1                     |